

GRENVO ATF D-III

GRENVO ATF D-III is a high-quality automatic transmission fluid manufactured from highly refined base stock and carefully selected additives, to provide a superior performance in the automatic transmission systems of automotive.

Approvals & Recommendations

DEXRON® D-III

Features/Benefits

Longer Service Intervals.

Enhanced Oxidation and thermal stability to reduce deposit formation.

Superior Anti-wear protection.

Super friction durability and foam control.

Provides good protection against rust and corrosion.

Application

ATF III D is recommended for Automatic Transmissions and Power Steering Systems of vehicles requiring GM DEXRON® III G/F, DEXRON® IIE/D, Type A Suffix A quality fluids.

It is also recommended for power steering, torque converters and hydraulic systems, where such types of fluids are specified.



+971 65592441 (EXT.-106)



info@grenvolubetech.com



www.grenvolubetech.com

PRODUCT DATA SHEET



Typical Specifications

CONTROL ANALYSIS	TEST METHOD	ATF D-III
APPEARANCE	Visual	Clear & Bright
DENSITY AT 29.5 °C	ASTM D-1298	0.8257
VISCOSITY @ 100 °C, cSt	ASTM D-445	6.83
VISCOSITY @ 40 °C, cSt	ASTM D-445	29.24
VIS INDEX	ASTM D-2270	205
FLASH POINT COC °C	ASTM D-92	190
POUR POINT °C	ASTM D-97	-39
COLOUR	ASTM D-1500	Red



+971 65592441 (EXT.-106)



info@grenvolubetech.com



www.grenvolubetech.com

(An ISO 9001:2015, ISO14001:2015 & ISO 45001:2018 Certified Company)