

PRODUCT DATA SHEET



GRENVO ATF D-VI

Grenvo ATF VI is a fully synthetic automatic transmission fluid developed for GM-made 6 speed transmissions. Dexron VI specification products are high quality fluids which have been providing service to automobiles since 2005. The product is made using Group III base oil and specialised additives such as corrosion and rust inhibitors, friction modifiers. Will work in low temperatures down to (-) 40°C. GRENVO ATF D-IV has a drain interval of up to 160,000 KMs.

Approvals & Recommendations

DEXRON®D-VI

Features/Benefits

Long drain transmission oil. Excellent oxidation stability. Controlled friction. High VI Synthetic formulation provides for large temperature range and thermal stability. Anti-wear protection. Low temperature operation.



+971 65592441 (EXT.-106)



info@grenvolubetech.com



www.grenvolubetech.com

(An ISO 9001:2015, ISO14001:2015 & ISO 45001:2018 Certified Company)

PRODUCT DATA SHEET



Application

Hydraulic, Mechanical conventional & modern GM transmissions in cars and trucks and as a Power steering & hydraulic fluid in on-road vehicles.

Applications in off-road machinery in line with manufacturers' recommendations. Especially in applications requiring Low Viscosity fluid.

Hydraulic systems and all applications needing a VI / Allison C4 fluid.

Typical Specifications

Control Analysis	Test Method	Typical
KV, cSt, 40 Deg C	ASTM D445	29.9
KV, cSt, 100 Deg C	ASTM D445	5.9
Viscosity Index	ASTM D2270	170
Flash Point, COC, Deg C	ASTM D92	208
Pour Point, Deg C	ASTM D97	(-) 48
Density @ 15.6 Deg C, gmc/cc	ASTM D4052	0.845
Brookfield Visc. @ -40 Deg C	ASTM D2983	13,000 mPa.s



+971 65592441 (EXT.-106)



info@grenvolubetech.com



www.grenvolubetech.com