

PRODUCT DATA SHEET



GRENVO SLYDE 4T SAE 20W-50 API SM JASO MA-2

GRENVO SLYDE 4T SAE 20W-50 API SM JASO MA-2 is a unique lubricant ideal for high performance motorbikes manufacturers where SAE 20W-50 oil is recommended.

Approvals & Recommendations

JASO MA-2

SAE 20W-50

Features/Benefits

Keep engine clean without corrosion, protecting engine and gearbox in one circulation system.

Instant engine protection from heat-activated anti-wear molecule.

Prevent clutch slippage.

Provide outstanding oxidation stability.

Increases fuel economy.

Application

GRENVO SLYDE 4T SAE 20W-50 API SM JASO MA-2 grade is best for modern four-stroke motorcycle engines. Good protection to motorcycle engines before introduction of JASO MA or JASO MA-2.



+971 65592441 (EXT.-106)



info@grenvolubetech.com



www.grenvolubetech.com

(An ISO 9001:2015, ISO14001:2015 & ISO 45001:2018 Certified Company)

PRODUCT DATA SHEET



Typical Specifications

CONTROL ANALYSIS	TEST METHOD	SAE 20W-50 API SM JASO MA-2
APPEARANCE	Visual	Clear & Bright
DENSITY AT 29.5 °C	ASTM D-1298	0.8661
VISCOSITY @ 100 °C, cSt	ASTM D-445	19.10
VISCOSITY @ 40 °C, cSt	ASTM D-445	164.0
VIS INDEX	ASTM D-2270	133
FLASH POINT COC °C	ASTM D-92	230
POUR POINT °C	ASTM D-97	-21
TBN, mg.KOH/g	ASTM D-2896	6.0



+971 65592441 (EXT.-106)



info@grenvolubetech.com



www.grenvolubetech.com

(An ISO 9001:2015, ISO14001:2015 & ISO 45001:2018 Certified Company)